

WASHER EXTRACTORS TECHNICAL DATA

	UNIT.	HIGH SPIN									
		WED-11	WED-14	WED-18	WED-27	WED-35C	WED-45C	WED-60	WED-100C	WED-120C	
DRUM											
Load capacity 1:9	Kg	11	14	20	28	39	47	67	105	128	
Load capacity 1:10	Kg	10	13	18	25	35	42	60	95	115	
Volume	lt	100	130	180	250	350	420	600	950	1.150	
Diameter	mm	532	620	700	770	860	860	1.048	1360	1.360	
Depth	mm	425	430	470	530	602	723	684	654	792	
GENERAL DETAILS											
Washing speed	r.p.m.	50	50	47	45	42,5	42,5	38	34	34	
Spining speed	r.p.m.	1.231	1.138	1.071	1.024	966	966	875	678	678	
Factor G	-	450	450	450	450	450	450	450	350	350	
Noise level	dB	< 70	< 70	< 70	< 70	< 70	< 70	< 70	< 70	< 70	
Self-service version	-	YES	YES	YES	YES	YES	NO	NO	NO	NO	
Double drainage	-	EXTER. - OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	
Weighing System	-	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	OPT	
Tilting System	-	NO	NO	NO	NO	NO	NO	OPT	OPT	OPT	
Option SLUICE	-	NO	NO	NO	NO	NO	NO	NO	NO	NO	
DOOR											
Height center door	mm	630	700	765	865	885	885	1.190	1.330	1.330	
Height base door	mm	370	440	450	560	540	540	830	900	900	
Diameter	mm	373	373	460	460	560	560	560	700	700	
POWER											
Motor	Kw	0,75	1,1	2,2	4	6	6	11	15	15	
Heating (Electric model)	Kw	6	9	12	18	21	21	36	-	-	
Max. power (Electric model)	Kw	6,25	9,4	12,75	19,2	23	23	40	-	-	
Max. power (Steam model and hot water)	Kw	0,75	1,1	2,2	4	6	6	11	15	15	
CONNECTIONS											
Steam inlet	inch	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	3/4"	1-1/4"	1-1/4"	
Water inlet	inch	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	1"	1-1/2"	1-1/2"	
Drain	inch	3"	3"	3"	3"	3"	3"	3"	4"	4"	
DIMENSIONS											
Width	mm	692	788	884	979	1.095	1.095	1.478	1.815	1.815	
Depth	mm	788	869	913	1.041	1.184	1.304	1.444	1.690	1.828	
Height	mm	1.185	1.307	1.415	1.553	1.598	1.598	1.945	2.245	2.245	
Net weight	Kg	230	250	360	490	750	800	1.400	3.900	3.950	
PACKING DIMENSIONS											
Width	mm	730	850	945	1.040	1.165	1.165	1.540	1.900	1.900	
Depth	mm	1.000	1.010	1.030	1.160	1.230	1.480	1.580	1.940	1.940	
Height	mm	1.417	1.560	1.700	1.850	1.920	1.920	1.970	2.290	2.290	
Gross weight	Kg	239	283	393	545	820	870	1.520	4.050	4.100	
Volume	m³	1,03	1,34	1,65	2,23	2,75	3,31	4,79	8,44	8,44	

	UNIT.	MEDIUM SPIN				LOW SPIN						
		WEM-11	WEM-14	WEM-18	WEM-27	WEN-11	WEN-14	WEN-18	WEN-27	WEN-35C	WEN-45C	WEN-60
DRUM												
Load capacity 1:9	Kg	11	14	20	28	11	14	20	28	39	47	67
Load capacity 1:10	Kg	10	13	18	25	10	13	18	25	35	42	60
Volume	lt	100	130	180	250	100	130	180	250	350	420	600
Diameter	mm	620	620	700	770	620	620	700	770	860	860	1048
Depth	mm	330	430	470	530	330	430	470	530	602	723	684
GENERAL DETAILS												
Washing speed	r.p.m.	50	50	47	40	50	50	47	40	45	45	42,5
Spining speed	r.p.m.	932	929	874	836	762	762	714	682	644	644	505
Factor G	-	300	300	300	300	200	200	200	200	200	200	150
Noise level	dB	< 70	< 70	< 70	< 70	< 70	< 70	< 70	< 70	< 70	< 70	< 70
Self-service version	-	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
Double drainage	-	OPT (external)	OPT (external)	OPT	OPT	NO	OPT	OPT	OPT	OPT	OPT	OPT
Weighing System	-	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
Tilting System	-	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
Option SLUICE	-	NO	NO	NO	NO	YES	YES	YES	YES	YES	YES	NO
DOOR												
Height center door	mm	570	570	655	700	570	570	655	700	735	735	900
Height base door	mm	310	310	348	400	310	310	348	400	440	440	540
Diameter	mm	373	373	460	460	373	373	460	460	560	560	560
POWER												
Motor	Kw	1,1	1,1	2,2	3	1,1	1,1	2,2	3	4	6	5,5
Heating (Electric model)	Kw	6	9	12	18	6	9	12	18	21	21	36
Max. power (Electric model)	Kw	6,3	9,5	12,75	19	6,3	9,5	12,75	19	22	23	38
Max. power (Steam model and h. w.)	Kw	1,1	1,1	2,2	3	1,1	1,1	2,2	3	4	6	5,5
CONNECTIONS												
Steam inlet	inch	1/2"	1/2"	1/2"	3/4"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	3/4"
Water inlet	inch	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Drain	inch	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"
DIMENSIONS												
Width	mm	719	719	788	884	719	719	788	884	979	979	1225
Depth	mm	684	830	840	1.011	684	830	840	965	1.066	1.200	1.279
Height	mm	1.158	1.158	1.307	1.340	1.158	1.158	1.307	1.340	1.411	1.411	1.640
Net weight	Kg	217	239	281	340	217	239	281	340	473	523	930
PACKING DIMENSIONS												
Width	mm	800	800	840	930	800	800	840	930	1.050	1.050	1.360
Depth	mm	990	990	1.010	1.150	990	990	1.010	1.150	1.250	1.480	1.480
Height	mm	1.350	1.350	1.500	1.523	1.350	1.350	1.500	1.523	1.670	1.670	1.880
Gross weight	Kg	225	247	301	370	225	247	301	370	503	553	1.050
Volume	m³	1,07	1,07	1,27	1,63	1,07	1,07	1,27	1,63	2,19	2,59	3,78

DANUBE reserves the right to modify the technical data without notice.